






Ordering Information:

C3030WVA--2xXP - * - **
1 2 3

1.Part No.

2.Style:

(blank): Type 1

3: Type 3

3.Finish:

(blank):Tin over Nickel


G:Gold-flash

G15:15µin (0.38µm) MIN.Select Gold

100µin (2.54µm) MIN.Select Tin

G30:30µin (0.76µm) MIN.Select Gold

100µin (2.54µm) MIN.Select Tin



SPECIFICATIONS:

Current Rating: 12.5A AC,DC (AWG #18)

Voltage Rating: 600V AC,DC

Temperature Range: -40°C ~ +265°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min



Withstanding Voltage: 1500V AC/minute

Pin Material: Brass/Tin over Nickel

Material:Nylon 46,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2x1P	---	6.70	2x7P	18.00	24.70
2x2P	3.00	9.70	2x8P	21.00	27.70
2x3P	6.00	12.70	2x9P	24.00	30.70
2x4P	9.00	15.70	2x10P	27.00	33.70
2x5P	12.00	18.70	2x11P	30.00	36.70
2x6P	15.00	21.70	2x12P	33.00	39.70



A3	CHANGE THE DRAWING	2022.01.15
A2	CHANGE THE Current Rating	2018.12.26
A1	Modify the size	2017.02.20
A0	NEW RELEASE	2016.12.06
REV	DESCRIPTION	DATE

Beijing Hongli Kunpeng International Trade Co.,Ltd.

Unit	Scale	Sheet	TITLE	
mm	3:1	1 of 1		
DRWN	CHK'D	APPR	3.00mm PITCH VERTICAL Dual Row WAFER	
Xu Lei	DianKui Wan	Jack Yin		
General Tolerances		THIRD ANGLE PROJECTION	DRAWING NO.	REV
x.xx±0.25 x.xxx±0.20 x.xxxx±0.15 ANGLES ±1°			HLB-30-WVA-2xXP 12	A3