


HLAL Series

DIN41612 B Simple Type Female

Drawing NO. : DIN152

UNIT:mm



MATERIAL:

Contacts:Brass

Housing:PBT UL 94V-0

ELECTRICAL CHARACTERISTICS:

Current Rating:2 A

Dielectric Withstanding Voltage:AC 1000V

Insulator Resistance:1000 M Ω min

Contact Resistance:30 m Ω max

Operating Temperature:-55° C~+105° C

Pitch	Position	Rows with Contacts	Contact Arrange
2.54mm	64	a b	
	32	a -	
5.08mm	32	a b	
	16	a -	

ORDERING INFORMATION

Series N.O	Pitch(mm)	Contact Type	Position	Contact length(mm)	Contact Plating	Glod Plating	Dip Type
HLAL -	*	2	*	*	*	*	D1
DIN41612 B Type	3: 2.54 4: 5.08	2:Female	64 32 16	1: 4.0	C: Dip Tin Comtact Gold G: Glod	00: G/F 02: 2u" 03: 3u" 05: 5u" 10: 10u" 15:15u" 30: 30u"	Simple type

Tel: 86-10-57891098 MP :86-13001179378 or 13146881693

Mail: info@hlkpint. com or lucyliu0807 @163.com