



HLAL Series

DIN41612 R Type Male

Drawing NO. : DIN083

UNIT:mm



MATERIAL:

Contacts:Brass
Housing:PBT UL 94V-0

ELECTRICAL CHARACTERISTICS:

Current Rating:2 A
Dielectric Withstanding Voltage:AC 1000V
Insulator Resistance:1000 M Ω min
Contact Resistance:30 m Ω max
Operating Temperature:-55° C~+105° C

Pitch	Position	Length	1	2	3	4
			4.0	13.0	15.0	17.0
2.54mm	30		a b c			
	20		a b -			
	20		a - c			
	10		a - -			
5.08mm	15		a b c			
	10		a b -			
	10		a - c			
	5		a - -			

ORDERING INFORMATION

Series N.O	Pitch(mm)	Contact Type	Position	Contact length(mm)	Contact Plating	Glod Plating	Dip Type
HLAL -	*	3	*	*	*	*	D
DIN41612 R Type	1: 2.54 2: 5.08	3:Male	30 20 15 10 5	1: 4.0 2: 13.0 3: 15.0 4: 17.0	C: Dip Tin Contact Gold G: Glod	00: G/F 02: 2u" 03: 3u" 05: 5u" 10: 10u" 15:15u" 30: 30u"	Blank: Dip

Tel: 86-10-57891098 MP :86-13001179378 or 13146881693

Mail: info@hlkpint. com or lucyliu0807 @163.com