

KAQY214 Series

4PIN 400V N.O TYPE

SOLID STATE RELAY-MOSFET Output

● Description

The KAQY214 series is robust, ideal for telecom and ground fault applications. It is a SPST normally open switch (1 Form A) that replaces electromechanical relays in many applications. It is constructed using a GaAlAs LED for actuation control and an integrated monolithic die for the switch output. The die, fabricated in a high-voltage dielectrically isolated technology, is comprised of a photodiode array, switch control circuitry and MOSFET switches.


● Features

1. Normally open, single pole single throw
2. Control 400V AC or DC voltage
3. Switch 130mA loads
4. Controls low-level analog signals
5. High sensitivity, low ON resistance
6. Low-level off-state leakage current
7. High isolation voltage 5KV (DIP / SMD)
8. Pb free and RoHS compliant
9. MSL class 1
10. Agency Approvals :
 - UL Approved (No. E108430): UL508
 - c-UL Approved (No. E108430)
 - FIMKO Approved: EN62368-1, EN60601-1
 - VDE Approved (No. 40053989): EN60747-5-5


● Application

- Telecommunications (PC, electronic notepad)
- Modem
- Telephone equipment
- Security equipment
- Sensors
- Measuring and testing equipment
- Factory automation equipment
- High speed inspection machines

● Schematic



1 FORM A
NORMALLY OPEN



KAQY214 Series

4PIN 400V N.O TYPE
SOLID STATE RELAY-MOSFET Output


● Outside Dimension

Unit : mm

1. Dual-in-line type.




KAQY214




2. Surface mount type.




KAQY214A



3. Small outline for surface mount type.




KAQY214S



TOLERANCE : $\pm 0.2\text{mm}$

● Device Marking



Notes :

cosmo

Y214

Y214S

YWW

(Blank) : DIP or SMD

S : SOP

Y : Year code / W : Week code

KAQY214 Series

4PIN 400V N.O TYPE

SOLID STATE RELAY-MOSFET Output

● Absolute Maximum Ratings

(Ta=25°C)


Item	Symbol	Rating	Unit
Input	Continuous forward current	I_F	50
	Peak forward current	I_{FP}	1
	Reverse voltage	V_R	5
	Power dissipation	P_{in}	100
	Derate linearly from 25°C	-	1.3
Output	Breakdown voltage	V_B	400
	Continuous load current	I_L	130
	Power dissipation	P_{out}	500
Isolation voltage		V_{iso}	KAQY214S
			KAQY214
		1500Vrms	5000Vrms
Isolation resistance ($V_{io}=500V$)		R_{iso}	$\geq 10^{10}$
			Ω
Total power dissipation		P_t	550
			mW
Derate linearly from 25°C		-	2.5
			mW/°C
Operating temperature		T_{opr}	-40 to +85
			°C
Storage temperature		T_{stg}	-40 to +125
			°C
Junction temperature		T_j	100
			°C
Soldering temperature 10 seconds		T_{sot}	260
			°C

● Electro-optical Characteristics

(Ta=25°C)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Input	Forward voltage	V_F	$I_F=10mA$	-	1.2	1.5
	Operation input current	I_{FON}	$V_L=20V, I_L=100mA$	-	-	3.0
	Recovery input current	I_{FOFF}	$V_L=20V, I_L \leq 5\mu A$	0.2	-	-
Output	Breakdown voltage	V_B	$I_B=50\mu A$	400	-	-
	Off-state leakage current	I_{LEAK}	$V_L=400V, I_F=0mA$	-	0.2	1.0
I/O capacitance		C_{iso}	$V_B=0V, f=1MHz$	-	6	-
						pF
ON resistance		R_{ON}	$I_F=10mA, I_L=100mA$	-	20	30
						Ω
Turn-on time		T_{ON}	$I_F=10mA, V_L=20V$	-	0.3	1.0
						ms
Turn-off Time		T_{OFF}	$I_L=100mA, t=10ms$	-	0.1	1.0
						ms



● Turn-on / Turn-off Time



KAQY214 Series

4PIN 400V N.O TYPE
SOLID STATE RELAY-MOSFET Output

● Schematic and Wiring Diagrams

Schematic	Output Configuration	Load	Connection	Wiring Diagrams
	1a	AC DC		

KAQY214 Series

4PIN 400V N.O TYPE
SOLID STATE RELAY-MOSFET Output

Fig.1 Load Current vs. Ambient Temperature




Fig.2 On Resistance vs. Ambient Temperature




Fig.3 Turn-on Time vs. Ambient Temperature




Fig.4 Turn-off Time vs. Ambient Temperature




Fig.5 LED Operate Current vs. Ambient Temperature





Fig.6 LED Turn-off Current vs. Ambient Temperature



KAQY214 Series

4PIN 400V N.O TYPE
SOLID STATE RELAY-MOSFET Output

Fig.7 LED Dropout Voltage vs. Ambient Temperature




Fig.8 Voltage vs. Current Characteristics of Output at MOSFET Portion




Fig.9 Turn-on Time vs. LED Forward Current




Fig.10 Off-state Leakage Current vs. Load Voltage




Fig.11 Turn-off Time vs. LED Forward Current





Fig.12 Output Capacitance vs. Applied Voltage



KAQY214 Series


4PIN 400V N.O TYPE
SOLID STATE RELAY-MOSFET Output

● Using Methods



Examples of resistance value to control LED forward current ($I_F=5\text{mA}$)



1. LED forward current must be more than 5mA , at E min.
2. LED forward current must be less than 50mA , at E max.



Regulate the spike voltage generated on the inductive load as follows :




● **Recommended Soldering Conditions**

(a) **Infrared reflow soldering :**

- | | |
|--|---|
| ■ Peak reflow soldering : | 260°C or below (package surface temperature) |
| ■ Time of peak reflow temperature: | 10 sec |
| ■ Time of temperature higher than 230°C : | 30-60 sec |
| ■ Time to preheat temperature from 180~190°C : | 60-120 sec |
| ■ Number of reflows : | Two |
| ■ Flux : | Rosin flux containing small amount of chlorine
(The flux with a maximum chlorine content of 0.2 Wt% is recommended.) |

Recommended Temperature Profile of Infrared Reflow



(b) **Wave soldering :**

- | | |
|--------------------------|--|
| ■ Temperature : | 260°C or below (molten solder temperature) |
| ■ Time : | 10 seconds or less |
| ■ Preheating conditions: | 120°C or below (package surface temperature) |
| ■ Number of times : | One |
| ■ Flux : | Rosin flux containing small amount of chlorine (The flux with a maximum chlorine content of 0.2 Wt% is recommended.) |

(c) **Cautions :**

- | | |
|------------|--|
| ■ Fluxes : | Avoid removing the residual flux with freon-based and chlorine-based cleaning solvent. |
| ■ | Avoid shorting between portion of frame and leads. |

KAQY214 Series

4PIN 400V N.O TYPE
SOLID STATE RELAY-MOSFET Output

● Numbering System

KAQY214 X (Y)

Note :

KAQY214 = Part No.

X = Lead form option (blank 、 S or A)


Y = Tape and reel option (TLD 、 TRU)

Option	Description	Packing quantity
A (TLD)	surface mount type package + TLD tape & reel option	2000 units per reel
A (TRU)	surface mount type package + TRU tape & reel option	2000 units per reel
S (TLD)	small outline for surface mount type package + TLD tape & reel option	3000 units per reel
S (TRU)	small outline for surface mount type package + TRU tape & reel option	3000 units per reel

● Recommended Pad Layout for Surface Mount Lead Form


1. Surface mount type.

4-pin SMD



2. Small outline for surface mount type.

4-pin SOP




Unit : mm

KAQY214 Series

4PIN 400V N.O TYPE
SOLID STATE RELAY-MOSFET Output

● 4-pin SMD Carrier Tape & Reel



KAQY214 Series

4PIN 400V N.O TYPE
SOLID STATE RELAY-MOSFET Output

● 4-pin SOP Carrier Tape & Reel

