

KAQV253 Series


6PIN 250V N.O TYPE

SOLID STATE RELAY-MOSFET OOUTPUT


● Description

The KAQV253 series is robust, ideal for telecom and ground fault applications. It is a SPST normally open switch (1 Form A) that replaces electromechanical relays in many applications. It is constructed using a GaAlAs LED for actuation control and an integrated monolithic die for the switch output. The die, fabricated in a high-voltage dielectrically isolated technology, is comprised of a photodiode array, switch control circuitry and MOSFET switches.

● Schematic



1 FORM A
NORMALLY OPEN



● Features

1. Normally open, single pole single throw
2. Control 250V AC or DC voltage
3. Switch 200mA loads
4. Controls low-level analog signals
5. High sensitivity, low ON resistance
6. Low-level off-state leakage current
7. High isolation voltage 5KV
8. Pb free and RoHS compliant
9. MSL class 1
10. Agency Approvals :
 - UL Approved (No. E169586, E108430): UL1577, UL508
 - c-UL Approved (No. E169586, E108430)
 - VDE Approved (No. 40053989): EN60747-5-5

● Application

- Telecommunications (PC, electronic notepad)
- Modem
- Telephone equipment
- Security equipment
- Sensors
- Measuring and testing equipment
- Factory automation equipment
- High speed inspection machines

KAQV253 Series


6PIN 250V N.O TYPE

SOLID STATE RELAY-MOSFET OOUTPUT


● Outside Dimension

Unit : mm


1. Dual-in-line type.




KAQV253



2. Surface mount type.



KAQV253A



TOLERANCE : $\pm 0.2\text{mm}$

● Device Marking



Notes :

Cosmo

V253 ☐ ☐ (Blank) : DIP or SMD forming
YWW Y : Year code / W : Week code

KAQV253 Series

6PIN 250V N.O TYPE
SOLID STATE RELAY-MOSFET OOUTPUT

● Absolute Maximum Ratings

(Ta=25°C)


Item	Symbol	Rating	Unit
Input	Continuous forward current	I _F	50
	Peak forward current	I _{FP}	1
	Reverse voltage	V _R	5
	Power dissipation	P _{in}	100
	Derate linearly from 25°C	-	1.3
Output	Breakdown voltage	V _B	250
	Continuous load current	I _L	200
	Power dissipation	P _{out}	500
Isolation voltage		V _{iso}	5000
Isolation resistance (Vio=500V)		R _{iso}	≥ 10 ¹⁰
Total power dissipation		P _t	550
Derate linearly from 25°C		-	2.5
Operating temperature		T _{opr}	-40 to +85
Storage temperature		T _{stg}	-40 to +125
Junction temperature		T _j	100
Soldering temperature 10 seconds		T _{sot}	260

● Electro-optical Characteristics

(Ta=25°C)

Parameter			Symbol	Conditions	Min.	Typ.	Max.	Unit
Input	Forward voltage		V _F	I _F =10mA	-	1.2	1.5	V
	Operation input current		I _{FON}	V _L =20V, I _L =100mA	-	-	3.0	mA
	Recovery input current		I _{FOFF}	V _L =20V, I _L ≤5μA	0.2	-	-	mA
Output	Breakdown voltage		V _B	I _B =50μA	250	-	-	V
	Off-state leakage current		I _{LEAK}	V _L =250V, I _F =0mA	-	0.2	1.0	μA
I/O capacitance			C _{iso}	V _B =0V, f=1MHz	-	6	-	pF
ON resistance	Connection	A	R _{ON}	I _F =10mA, I _L =100mA	-	5	8	Ω
		B			-	2.5	4	
		C			-	1.2	2	
Turn-on time			T _{ON}	I _F =10mA, V _L =20V	-	0.3	1.0	ms
Turn-off time			T _{OFF}	I _L =100mA, t=10ms	-	0.1	1.5	ms

● Turn-on / Turn-off Time



KAQV253 Series

6PIN 250V N.O TYPE
SOLID STATE RELAY-MOSFET OOUTPUT

● Schematic and Wiring Diagrams

Schematic	Output Configuration	Load	Connection	Wiring Diagrams
	1a	AC DC	A	
		DC	B	
		DC	C	

KAQV253 Series

6PIN 250V N.O TYPE
SOLID STATE RELAY-MOSFET OOUTPUT

Fig.1 Load Current vs. Ambient Temperature




Fig.2 On Resistance vs. Ambient Temperature




Fig.3 Turn-on Time vs. Ambient Temperature




Fig.4 Turn-off Time vs. Ambient Temperature




Fig.5 LED Operate Current vs. Ambient Temperature





Fig.6 LED Turn-off Current vs. Ambient Temperature



KAQV253 Series

6PIN 250V N.O TYPE
SOLID STATE RELAY-MOSFET OOUTPUT

Fig.7 LED Dropout Voltage vs. Ambient Temperature




Fig.8 Voltage vs. Current Characteristics of Output at MOSFET Portion




Fig.9 Turn-on Time vs. LED Forward Current




Fig.10 Off-state Leakage Current vs. Load Voltage




Fig.11 Turn-off Time vs. LED Forward Current





Fig.12 Output Capacitance vs. Applied Voltage




KAQV253 Series

6PIN 250V N.O TYPE

SOLID STATE RELAY-MOSFET OOUTPUT


● Using Methods

Examples of resistance value to control LED forward current ($I_F=5\text{mA}$)





E	R
3.3V	Approx. 330 Ω
5V	Approx. 640 Ω
12V	Approx. 1.9K Ω
15V	Approx. 2.5K Ω
24V	Approx. 4.1K Ω

1. LED forward current must be more than 5mA , at E min.
2. LED forward current must be less than 50mA , at E max.



Regulate the spike voltage generated on the inductive load as follows :




R-C Snubber

● **Recommended Soldering Conditions**

(a) Infrared reflow soldering :

- | | |
|--|--|
| ■ Peak reflow soldering : | 260°C or below (package surface temperature) |
| ■ Time of peak reflow temperature: | 10 sec |
| ■ Time of temperature higher than 230°C : | 30-60 sec |
| ■ Time to preheat temperature from 180~190°C : | 60-120 sec |
| ■ Number of reflows : | Two |
| ■ Flux : | Rosin flux containing small amount of chlorine (The flux with a maximum chlorine content of 0.2 Wt% is recommended.) |

Recommended Temperature Profile of Infrared Reflow



(b) Wave soldering :

- | | |
|--------------------------|--|
| ■ Temperature : | 260°C or below (molten solder temperature) |
| ■ Time : | 10 seconds or less |
| ■ Preheating conditions: | 120°C or below (package surface temperature) |
| ■ Number of times : | One |
| ■ Flux : | Rosin flux containing small amount of chlorine (The flux with a maximum chlorine content of 0.2 Wt% is recommended.) |

(c) Cautions :

- | | |
|------------|--|
| ■ Fluxes : | Avoid removing the residual flux with freon-based and chlorine-based cleaning solvent. |
| ■ | Avoid shorting between portion of frame and leads. |

KAQV253 Series

6PIN 250V N.O TYPE
SOLID STATE RELAY-MOSFET OOUTPUT

● Numbering System

KAQV253 X (Y)

Note :

KAQV253 = Part No.


X = Lead form option (blank or A)

Y = Tape and reel option (TL 、 TR)

Option	Description	Packing quantity
A (TL)	surface mount type package + TL tape & reel option	1000 units per reel
A (TR)	surface mount type package + TR tape & reel option	1000 units per reel

● Recommended Pad Layout for Surface Mount Lead Form

6-pin SMD




Unit : mm

KAQV253 Series

6PIN 250V N.O TYPE
SOLID STATE RELAY-MOSFET OOUTPUT

● 6-pin SMD Carrier Tape & Reel

Unit : mm



TOLERANCE : $\pm 0.2\text{mm}$

